

ICHIRO SEIRYU ICR-1421

PCMO - API SL ACEA A5/B5

Description

説明

Fully Synthetic passenger car motor oil formulated with premium base oils and advanced additive technology. It meets American Petroleum Institute (API) standards, providing superior oxidation resistance, high thermal stability, making it well-suited for modern engines.

The formulation complies with European Automobile Manufacturers' Association (ACEA) specifications, supporting fuel efficiency and maintaining low Noack volatility to reduce hydrocarbon tailpipe emissions. By minimizing friction and conserving energy, it enhances engine efficiency while ensuring reliable lubrication of all engine components.

Benefits

特典

- △ Ensures reliable protection for engines
- △ Minimizes contamination and sludge formation
- △ Effectively controls wear and piston deposits
- △ Prevents rust and corrosion of metal surfaces

Typical Characteristics

典型的な特徴

Test Description	Method	Unit	ICR-
SAE Viscosity Grade	SAE J 300	-	5W30
Density @ 15 °C	ASTM D 4052	kg/L	0.857
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-39
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	62.5
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	10.9
Viscosity Index	ASTM D 2270	-	166
TBN	ASTM D 2896	mgKOH/g	12.5

Specifications & Recommendations

仕様と推奨事項

△ API	SL
△ ACEA	A5/B5
△ FORD	WSS-M2C913-D
△ RENAULT	0700
△ STJLR	03.5003

最後の変更: 04-09-25
整理番号: 5176G3SLA5B5REV0